



**QQFU2.E127738
Power Supplies, General Purpose - Component**

[Page Bottom](#)

Power Supplies, General Purpose - Component

[See General Information for Power Supplies, General Purpose - Component](#)

MEAN WELL ENTERPRISES CO LTD
28 WUQUAN 3RD RD WUGU DIST
NEW TAIPEI, 248 TAIWAN

E127738

Model No.	Rated Input			Max Output						OC	SP	EP	FC	GC
	Volts	Hz	SC	V	A	VA								
COMPONENT - POWER SUPPLY, GENERAL PURPOSE.														
HLG-240H(+)-12(*)														
	100-240/ 277ac	50/60	0	13.3dc	19.1	254	4	1012	20B	0	0			
HLG-240H(+)-15(*)														
	100-240/ 277ac	50/60	0	16.6dc	16.1	267.3	4	1012	20B	0	0			
HLG-240H(+)-20(*)														
	100-240/ 277ac	50/60	0	22.3dc	13.58	302.8	4	1012	20B	0	0			
HLG-240H(+)-24(*)														
	100-240/ 277ac	50/60	0	26.3dc	10.94	287.7	4	1012	20B	0	0			
HLG-240H(+)-30(*)														
	100-240/ 277ac	50/60	0	32.6dc	8.96	292	-	1012	20B	0	0			
HLG-240H(+)-36(*)														
	100-240/ 277ac	50/60	0	39.4dc	6.9	272	-	1012	20B	0	0			
HLG-240H(+)-42(*)														
	100-240/ 277ac	50/60	0	45.5dc	6.6	300	-	1012	20B	0	0			
HLG-240H(+)-48(*)														
	100-240/ 277ac	50/60	0	52.5dc	5.45	286	-	1012	20B	0	0			
HLG-240H(+)-54(*)														
	100-240/ 277ac	50/60	0	59.8dc	6.25	373.7	-	1012	20B	0	0			
CLG-150-12(*) (a)														
	100-240/ 277ac	50/60	0	12.12dc	11.9	139.2	4	1012	20B	0	0			
CLG-150-15(*) (a)														
	100-240/ 277ac	50/60	0	15.05dc	10.9	163.1	4	1012	20B	0	0			
CLG-150-20(*) (a)														
	100-240/ 277ac	50/60	0	20.2dc	8.1	163.2	4	1012	20B	0	0			
CLG-150-24(*) (a)														

	100-240/ 277ac	50/60	0	24.17dc	6.7	162.9	4	1012	20B	0	0
CLG-150-30(*) (a)											
	100-240/ 277ac	50/60	0	30.08dc	7.4	157.3	4	1012	20B	0	0
CLG-150-36(*) (a)											
	100-240/ 277ac	50/60	0	36.11dc	4.6	165.8	4	1012	20B	0	0
CLG-150-48(*) (a)											
	100-240/ 277ac	50/60	0	48.16dc	3.4	163.1	4	1012	20B	0	0
D-60A[*r]	100- 240ac	50-60	0	5	4	20	4	1012	20B	0	1
				12	3	36	4				
D-60B	100- 240ac	50-60	0	4.96	14.0	69.4	4	1012	20B	0	1
				23.19	3.18	73.7	4				
MWP-606	100-120/ 220- 240ac	50/60	0	4.98	16.20	80	4	1012	20B	0	1
				12.51	6.50	70	4				
				-5.20	6.80	29	4				
PS-280-13.5, SM-25[*r]											
	100-120/ 220- 240ac	50/60	0	13.5	20	270	4	1012	20B	0	1
PS-280-27, SM-1228[*r]											
	100-120/ 220- 240ac	50/60	0	27.0	10	270	4	1012	20B	0	1
S-100F-12											
	100-120/ 200- 240ac	50-60	0	13.8	13.2	156	4	1012	30B	0	1
S-100F-15											
	100-120/ 200- 240ac	50-60	0	15	8.36	117	4	1012	30B	0	1
S-100F-24											
	100-120/ 200- 240ac	50-60	0	28	6.4	157	4	1012	30B	0	1
S-100F-48											
	100-120/ 200- 240ac	50-60	0	48	2.86	137	4	1012	30B	0	1
S-100F-5											
	100-120/ 200- 240ac	50-60	0	5.8	29.1	125	4	1012	30B	0	1
S-100F-7.5											
	100-120/ 200- 240ac	50-60	0	8.8	18.3	134	4	1012	30B	0	1
S-150-12											
	100-120/ 220- 240ac	50/60	0	11.96	15.73	179	4	1012	20B	0	1
S-150-15[*r]											

	100-120/ 220- 240ac	50/60	0	15.0	10.00	150	4	1012	20B	0	1
S-150-24											
	100-120/ 220- 240ac	50/60	0	23.93	8.20	194	4	1012	20B	0	1
S-150-5	100-120/ 220- 240ac	50/60	0	5.0	34.73	168	4	1012	20B	0	1
S-150-7.5[*r]											
	100-120/ 220- 240ac	50/60	0	7.5	20.00	150	4	1012	20B	0	1
S-150-9[*r]	100-120/ 220- 240ac	50/60	0	9.0	16.70	150	4	1012	20B	0	1
S-25-12[*r]	100- 240ac	50-60	0	12.0	2.1	25.2	4	1012	20B	0	1
S-25-15[*r]	100- 240ac	50-60	0	24.0	1.7	40.8	4	1012	20B	0	1
S-25-24	100- 240ac	50-60	0	23.93	1.5	35.89	4	1012	20B	0	1
S-25-5	100- 240ac	50-60	0	4.99	6.2	30.38	4	1012	20B	0	1
S-40-12[*r]	100- 240ac	50-60	0	12.0	3.5	42.0	4	1012	20B	0	1
S-40-15[*r]	100- 240ac	50-60	0	15.0	2.8	42.0	4	1012	20B	0	1
S-40-24[*r]	100- 240ac	50-60	0	24.15	2.3	25.4	4	1012	20B	0	1
S-40-5	100- 240ac	50-60	0	4.97	10.2	50.69	4	1012	20B	0	1
S-60-12[*r]	100- 240ac	50-60	0	12.0	5.0	60.0	4	1012	20B	0	1
S-60-15[*r]	100- 240ac	50-60	0	15.0	4.0	60.0	4	1012	20B	0	1
S-60-24	100- 240ac	50-60	0	24.01	3.3	79.23	4	1012	20B	0	1
S-60-30	100- 240ac	50-60	0	24.0	2.5	60	4	1012	20B	0	1
S-60-5	100- 240ac	50-60	0	4.99	14.5	72.35	4	1012	20B	0	1
S-60LT	120- 240ac	50/60	0	8.2	11	77	4	1012	20B	2.6	1
				17.3	5	72	4				
T-60A	100- 240ac	50-60	0	4.96	14.5	71.9	4	1012	20B	0	1
				11.9	6.2	73.8	4				
T-60B[*r]	100- 240ac	50-60	0	5.0	5.0	25	4	1012	20B	0	1
				12.0	2.5	30	4				
				-12.0	0.5	6	4				
T-60C[*r]	100- 240ac	50-60	0	5	5	25	4	1012	20B	0	1
				15	2	30	4				
				-15	0.5	7.5	4				

[*r] - Output values are rated.

(*) - Can be A or B or C or Blank

(+) - May or may not contain the letter H

(a) - household use

Marking: Company name and model designation.

Last Updated on 2011-03-29

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright ?2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





QQFU8.E127738
Power Supplies, General Purpose Certified for Canada - Component

[Page Bottom](#)

Power Supplies, General Purpose Certified for Canada - Component

[See General Information for Power Supplies, General Purpose Certified for Canada - Component](#)

MEAN WELL ENTERPRISES CO LTD
 28 WUQUAN 3RD RD WUGU DIST
 NEW TAIPEI, 248 TAIWAN

E127738

Model No.	Rated Input			Max Output			OC	SP	EP	FC	GC
	Volts	Hz	SC	V	A	VA					
COMPONENT - POWER SUPPLY, GENERAL PURPOSE.											
HLG-240H(+)-12(*)											
	100-240/277ac	50/60	0	13.3dc	19.1	254	4	107.1	20B	0	0
HLG-240H(+)-15(*)											
	100-240/277ac	50/60	0	16.6dc	16.1	267.3	4	107.1	20B	0	0
HLG-240H(+)-20(*)											
	100-240/277ac	50/60	0	22.3dc	13.58	302.8	4	107.1	20B	0	0
HLG-240H(+)-24(*)											
	100-240/277ac	50/60	0	26.3dc	10.94	287.7	4	107.1	20B	0	0
HLG-240H(+)-30(*)											
	100-240/277ac	50/60	0	32.6dc	8.96	292	-	107.1	20B	0	0
HLG-240H(+)-36(*)											
	100-240/277ac	50/60	0	39.4dc	6.9	272	-	107.1	20B	0	0
HLG-240H(+)-42(*)											
	100-240/277ac	50/60	0	45.5dc	6.6	300	-	107.1	20B	0	0
HLG-240H(+)-48(*)											
	100-240/277ac	50/60	0	52.5dc	5.45	286	-	107.1	20B	0	0
HLG-240H(+)-54(*)											
	100-240/277ac	50/60	0	59.8dc	6.25	373.7	-	107.1	20B	0	0
CLG-150-12(*) (a)											
	100-240/277ac	50/60	0	12.12dc	11.9	139.2	4	-	-	0	0
CLG-150-15(*) (a)											


	100-240/277ac	50/60	0	15.05dc	10.9	163.1	4	-	-	0	0
CLG-150-20(*) (a)											
	100-240/277ac	50/60	0	20.2dc	8.1	163.2	4	-	-	0	0
CLG-150-24(*) (a)											
	100-240/277ac	50/60	0	24.17dc	6.7	162.9	4	-	-	0	0
CLG-150-30(*) (a)											
	100-240/277ac	50/60	0	30.08dc	7.4	157.3	4	-	-	0	0
CLG-150-36(*) (a)											
	100-240/277ac	50/60	0	36.11dc	4.6	165.8	4	-	-	0	0
CLG-150-48(*) (a)											
	100-240/277ac	50/60	0	48.16dc	3.4	163.1	4	-	-	0	0

(*) - Can be A or B or C or Blank

(+) - May or may not contain the letter H

(a) - household use



Marking: Company name, model designation and Recognized Component Mark for Canada, .
 Last Updated on 2011-03-29

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

